

APPLICATION UNDER UNITED STATES PATENT LAWS

Atty. Dkt. No. PW 280253
(M#)

Invention: LIQUID CRYSTAL DISPLAY ELEMENT AND METHOD OF MANUFACTURING THE SAME

Inventor (s): Toshiya OHTAKE
Yuzo HISATAKE
Atsuko OONO

Pillsbury Winthrop LLP
Intellectual Property Group
1100 New York Avenue, NW
Ninth Floor
Washington, DC 20005-3918
Attorneys
Telephone: (202) 861-3000

This is a:

- ☐ Provisional Application
- ☒ Regular Utility Application
- ☐ Continuing Application
☐ The contents of the parent are incorporated by reference
- ☐ PCT National Phase Application
- ☐ Design Application
- ☐ Reissue Application
- ☐ Plant Application
- ☐ Substitute Specification
Sub. Spec Filed _____
in App. No. _____ / _____
- ☐ Marked up Specification re
Sub. Spec. filed _____
In App. No. _____ / _____

SPECIFICATION

TITLE OF THE INVENTION
LIQUID CRYSTAL DISPLAY ELEMENT AND METHOD OF
MANUFACTURING THE SAME

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application is based upon and claims the
benefit of priority from the prior Japanese Patent
Application No. 2000-122928, filed April 24, 2000, the
entire contents of which are incorporated herein by
reference.

10 BACKGROUND OF THE INVENTION

 The present invention relates to a liquid crystal
display element, and more particularly, to a reflective
liquid crystal display element and a half-transmissive
liquid crystal display element, and a method of
15 manufacturing the same.

 These days, liquid crystal display elements are
applied to various fields including note-type personal
computers, display monitors, car navigation systems,
desk-top function calculators, medium- and small-sized
20 TV sets, etc. Among these display elements, reflective
liquid crystal display elements do not require use of a
backlight, so that they can enjoy low power consumption,
thinness, and lightness in weight. To make the most of
these advantages, the display elements of this type are
25 expected to be applied to displays for portable
apparatuses such as mobile personal computers.

 However, a conventional reflective liquid crystal

display element, like paper, is designed to utilize external light for display. If it is worked in a dark place, therefore, its display screen is too dark to be viewed with ease. It cannot be used at all in total darkness, in particular.

For this reason, the efficiency of light utilization of reflective liquid crystal display elements to be developed in the future should be as high as possible. The light utilization can be improved by optimizing a polarization plate, phase difference plate, color filter, etc., adopting a guest-host mode in which neither a polarization plate nor a phase difference plate is used, or developing reflective layers with high reflection efficiency.

A method is proposed in which a cholesteric liquid crystal is used for a high-reflection reflective layer. The cholesteric reflective layer serves to reflect circularly polarized light beams in a specific direction, out of light beams incident upon it. The wavelength zone of the reflected light varies depending on the helical pitch of the cholesteric liquid crystal. Accordingly, only light beams in a desired wavelength zone can be reflected if a plurality of cholesteric liquid crystal layers with different pitches are laminated to one another. If six or more layers are laminated, in particular, most of light beams in the visible light zone can be reflected.

These cholesteric reflective layers, compared with conventional metallic reflective layers of aluminum or the like, absorb less light, so that their light utilization is highly efficient.

5 On the other hand, a half-transmissive liquid crystal display element has been developed to solve the problem of the conventional reflective liquid crystal display element that cannot be used at all in total darkness. This half-transmissive element is provided with a backlight and a half-mirror for use as a half-transmissive reflective layer such that the element can be used as a transmissive liquid crystal display element in a dark place. Further, a half-transmissive liquid crystal display element is studied such that a pinhole is formed in the reflective layer for each pixel and a micro-lens is provided for each pixel. In the case where this liquid crystal display element is used as a reflective type, compared with the conventional reflective liquid crystal display element, the brightness of its display screen is lowered only by a margin corresponding to the pinhole. In the case where the display element is used as a transmissive type, a display screen as bright as that of the transmissive liquid crystal display element can be obtained if light emitted from a backlight is converged by means of a micro-lens and transmitted through the pinhole.

If the aforesaid cholesteric reflective layer is used as the reflective layer of the half-transmissive liquid crystal display element described above, moreover, the display element can enjoy high efficiency of light utilization and can be highly visible in both light and dark places.

In a liquid crystal display element, in general, however, the polarization plate, phase difference plate, liquid crystal layer, reflective layer, etc. are formed by laminating layers that have different positive or negative refractive index anisotropies. It is believed, therefore, that the luminance and chromaticity of the display element vary depending on the visual axis, frontal or oblique, and that the viewing angle of the display element is narrow.

This is a problem essential to the reflective and half-transmissive liquid crystal display elements that are expected to utilize external light and light from the backlight with high efficiency in the aforesaid manner. In the case where the cholesteric reflective layer, which generally has unique refractive index anisotropy, is used, in particular, it is believed to exhibit a unique viewing angle characteristic.

BRIEF SUMMARY OF THE INVENTION

The present invention has been contrived in consideration of these circumstances, and its object is to provide a liquid crystal display element, capable of

enjoying a display characteristic that hardly varies depending on the visual axis, frontal or oblique, and a manufacturing method therefor.

5 In order to achieve the above object, a liquid crystal display element according to the present invention comprises a polarization plate having a first average refractive index for a direction perpendicular to a display plane and a second average refractive index in a direction parallel to the display plane; a
10 phase difference plate having a first average refractive index for a direction perpendicular to the display plane and a second average refractive index for a direction parallel to the display plane; a liquid crystal layer having a first average refractive index
15 for a direction perpendicular to the display plane and a second average refractive index for a direction parallel to the display plane; and a selectively reflective layer for reflecting part or whole of circularly polarized light in a specific direction, the
20 selectively reflective layer having a first average refractive index for a direction perpendicular to the display plane and a second average refractive index for a direction parallel to the display plane. The polarization plate, phase difference plate, liquid
25 crystal layer, and selectively reflective layer are formed so that the absolute value of the sum total of the product of the thickness and the difference between

the first and second average refractive indexes of the polarization plate, the product of the thickness and the difference between the first and second average refractive indexes of the phase difference plate, the product of the thickness and the difference between the first and second average refractive indexes of the liquid crystal layer, and the product of the thickness and the difference between the first and second average refractive indexes of the selectively reflective layer is 50 nm or less.

According to the liquid crystal display element of the invention, the selectively reflective layer is formed of one or a plurality of layers of a cholesteric liquid crystal, and one or more layers having positive refractive index anisotropy are arranged adjacent to the reflective layer or with one or more organic layers being interposed therebetween.

According to the liquid crystal display element described above, at least one of the layers having positive refractive index anisotropy is formed of a discotic liquid crystal.

According to the liquid crystal display element described above, moreover, at least one of the layers having positive refractive index anisotropy includes a reflective layer for reflecting specifically polarized light, light in a specific wavelength zone, or specifically polarized light in a specific wavelength

zone only, out of incident light.

Another liquid crystal display element according to the invention comprises one or more reflective layers capable of reflecting specifically polarized light, light in a specific wavelength zone, or specifically polarized light in a specific wavelength zone only, out of incident light, the one or more reflective layers having positive refractive index anisotropy as a whole.

A method of manufacturing a liquid crystal display element according to the invention comprises vertically aligning a discotic liquid crystal doped with a chiral agent on a transparent first insulating substrate, thereby forming one or more reflective layers having positive refractive index anisotropy; opposing a transparent second insulating substrate to the first insulating substrate; and sealing in the a liquid crystal layer between the first and second insulating substrates.

Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate presently preferred embodiments of the invention, and together with the general description given above and the detailed description of the preferred embodiments given below, serve to explain the principles of the invention.

FIG. 1 is a sectional view of a half-transmissive liquid crystal display element according to an embodiment of the present invention;

FIG. 2 is a view for illustrating the principle of display for the case where the half-transmissive liquid crystal display element is used for transmissive display;

FIG. 3 is a view for illustrating the principle of display for the case where the half-transmissive liquid crystal display element is used for reflective display;

FIGS. 4A and 4B are diagrams for illustrating refractive index anisotropy;

FIG. 5 is a diagram for illustrating the viewing angle and retardation of layers having positive refractive index anisotropy; and

FIG. 6 is a diagram showing the result of subjective evaluation of the relation between retardation and visibility.

DETAILED DESCRIPTION OF THE INVENTION

A half-transmissive liquid crystal display element according to an embodiment of the present invention will now be described in detail with reference to the accompanying drawings.

As shown in FIG. 1, the liquid crystal display element comprises a lower substrate 1 and an upper substrate 11 that are opposed to each other. These substrates are formed of a transparent insulating substrate of, e.g., glass each. A phase difference plate 2 and a polarization plate 3 are arranged successively on the outer surface of the lower substrate 1. A first selectively reflective layer 4 having negative refractive index anisotropy, overcoat layer 5, second selectively reflective layer 6 having positive refractive index anisotropy, light diffusing layer 7, and transparent electrode 8 are formed successively in layers over the inner surface of the lower substrate 1.

A phase difference plate 12 and a polarization plate 13 are arranged successively over the outer surface of the upper substrate 11, and a liquid crystal driver circuit 10 including a color filter and a pixel electrode is provided on the inner surface of the substrate 11. A liquid crystal layer 9 is sealed in between the lower and upper substrates 1 and 11. Further, a backlight unit 14 is opposed to the outer

surface of the lower substrate 1.

The following is a detailed description of a configuration of the half-transmissive liquid crystal display element along with a manufacturing method therefor.

First, the first selectively reflective layer 4 is formed on the lower substrate 1. The layer 4, which has negative refractive index anisotropy, serves to reflect some, e.g., 70%, of circularly polarized light (right-handed circularly polarized light in this case) components of incident light in a specific direction and to transmit 30%, the remainder.

The first selectively reflective layer 4 may be formed of any material that has the aforesaid functions. According to the present embodiment, however, the layer 4 is a continuum formed of a cholesteric liquid crystal polymer layer capable of reflecting light in the ultraviolet zone and having helical pitches and a cholesteric liquid crystal polymer layer capable of reflecting light with wavelength of 600 nm and having helical pitches.

According to this arrangement, it is provided the first selectively reflective layer 4 wherein the helical pitches continuously change within the layer, owing to an interface interaction effect, and which can utilize light, in a wide range from the ultraviolet zone to the wavelength of 600 nm, for display. The

cholesteric liquid crystal polymer layer is formed by one or more cycles of operations including spin-coating, UV cross-linking, and thermal polymerization.

5 In forming the first selectively reflective layer 4, an alignment layer of polyimide or the like may be provided between the lower substrate 1 and the layer 4. The alignment layer serves steadily to orientate the cholesteric liquid crystal polymer layer and can
10 fulfill its selective reflection function without a loss.

Then, the second selectively reflective layer 6 is formed over the first selectively reflective layer 4 with the overcoat layer 5 between them. The overcoat layer 5, which serves to separate the first and second
15 selectively reflective layers 4 and 6, need not always be formed unless the function of the first layer 4 is ruined when the second layer 6 is formed on the first layer 4.

The second selectively reflective layer 6, like
20 the first selectively reflective layer 4, serves to reflect some, e.g., 70%, of circularly polarized light (right-handed circularly polarized light in this case) components of incident light in a specific direction and to transmit 30%, the remainder. However, it is
25 formed of a material with positive refractive index anisotropy.

The second selectively reflective layer 6 may be

formed of any material that has the aforesaid functions.
In this case, however, the layer 6 is a continuum
formed of a discotic liquid crystal polymer layer that
is twisted at pitches such that light with wavelength
of 600 nm is reflected and a discotic liquid crystal
polymer layer that is twisted at pitches such that
infrared light is reflected. According to this
arrangement, it is provided the second selectively
reflective layer 6 wherein the helical pitches
continuously change within the layer, owing to an
interface interaction effect, and that can utilize
light, in a wide range from the wavelength of 600 nm to
the infrared zone, for display.

Although the reflection wavelength zones for the
first and second selectively reflective layers 4 and 6
are set in the aforesaid manner according to the
present embodiment, the present invention is not
limited to this embodiment. For example, the
wavelength zones for selective reflection, compared
with those for the present embodiment, may be reversed
with respect to the first and second selectively
reflective layers 4 and 6 or arranged overlapping each
other. Alternatively, moreover, there may be
wavelength zones where light is reflected by neither of
the first and second layers 4 and 6 at all.

Further, one of the first and second selectively
reflective layers 4 and 6 need not be a selectively

reflective layer and may simply be a layer that has negative or positive refractive index anisotropy. Furthermore, the first and second layers 4 and 6 may be counterchanged in position. In either case, it is necessary only that layers that can reflect light of necessary wavelength zones according to the purpose of use of the liquid crystal display element and have negative and positive refractive index anisotropies be laminated to each other with the aid of an overcoat layer, if necessary.

Then, the light diffusing layer 7 is formed on the second selectively reflective layer 6. The diffusing layer 7 is formed by spin-coating and baking a dispersion of a transparent substance, such as titanium oxide, with particle diameters of, e.g., 0.01 to 5 μm , in a transparent organic material such as polyimide. A light diffusing layer with suitable light scattering properties can be obtained by adjusting the refractive indexes, shapes, and materials of the transparent substance and the transparent organic material or the particle diameters and mixture ratio of the transparent substance.

The light diffusing layer 7 may be formed on the side of the upper substrate 11, not on top of the second selectively reflective layer 6. Alternatively, a layer formed on a plastic film such as TAC may be pasted on the outer surface of the upper substrate 11.

Then, the transparent electrode 8 is formed on the light diffusing layer 7. Sputtering or spin-coating may be used as a method for forming the transparent electrode 8. If necessary, overcoat layers may be formed between the second selectively reflective layer 6, light diffusing layer 7, and transparent electrode 8.

A cell is assembled from the lower glass substrate 1 formed in this manner and the upper glass substrate 11, having the liquid crystal driver circuit 10 formed thereon by the conventional TFT (thin film transistor) process, and a liquid crystal is injected into the space between the glass substrates. In this case, an n-type nematic liquid crystal having negative refractive index anisotropy is used for the liquid crystal layer 9, and an alignment film is applied and rubbed to subject the liquid crystal molecules to vertical alignment before the cell is assembled.

According to the present embodiment, the aforesaid VA (vertical alignment) mode is adopted as the liquid crystal mode. Alternatively, however, a p-type nematic liquid crystal may be used, or the VA mode may be replaced with a homogeneous mode, HAN (hybrid alignment nematic) mode, IPS (in-plane switching) mode, or any other suitable liquid crystal mode.

After the liquid crystal is injected and subjected to a suitable heat treatment, the phase difference plates 2 and 12 and the polarization plates 3 and 13

are pasted on the respective outer surfaces of the lower and upper substrates 1 and 11, individually, and a peripheral circuit (not shown) for applying signals to the liquid crystal driver circuit 10 and the backlight unit 14 are mounted in place, whereupon the half-transmissive liquid crystal display element is completed.

Although the liquid crystal driver circuit 10 that includes TFTs and the like is formed on the upper substrate 11 according to the present embodiment, it may alternatively be incorporated in the lower substrate 1. In this case, the driver circuit 10 may be located under or between the first and second selectively reflective layers 4 and 6 so that the first and second layers 4 and 6 can be patterned partially or wholly to the pixel size. Further, the driver circuit 10 may be formed above the second selectively reflective layer 6.

According to the present embodiment, moreover, the liquid crystal driver circuit 10 has a COA (color-filter-on array) structure including a color filter. Alternatively, however, the color filter may be provided separately from switching elements such as the pixel electrode, TFT, etc. In this case, the color filter may be located in any position in an optical path for light that is conducive to display.

The following is a description of the principle of

display of the half-transmissive liquid crystal display element constructed in this manner. The principle of display for the case where the element is used as a transmissive liquid crystal display element will be described first.

As shown in FIG. 2, light emitted from the backlight unit 14 passes through the polarization plate 3 and the phase difference plate 2. In this case, the plates 3 and 2 are located so that the axis of absorption of the polarization plate 3 is inclined at an angle of 45° to the optical axis of the phase difference plate 2, and the retardation of the phase difference plate 2 is adjusted to $\lambda/4$. In this arrangement, the light transmitted through the plates 3 and 2 turns into circularly polarized light (right-handed circularly polarized light in this case) in a specific direction. 70% of the right-handed circularly polarized light is reflected by the first and second selectively reflective layers 4 and 6, and 30% is transmitted. The reflected and transmitted circularly polarized light components remain right-handed. The reflected light is reversely transmitted through the phase difference plate 2 and the polarization plate 3, reflected by the backlight unit 14, and guided again into the liquid crystal display element. As these processes are repeated, about 50% of the light emitted from the backlight unit 14 is finally transmitted

through the first and second selectively reflective layers 4 and 6.

If the aforesaid light is incident upon a pixel in which no voltage is applied to the liquid crystal layer 9 (off-state), the layer 9, which is located extending at right angles to the substrates 1 and 11, transmits the light as it is. The light is absorbed by the polarization plate 13 to establish black display, since the phase difference plate 12 and the polarization plate 13 are reversely arranged so that the angle between them is equal to the angle between the axis of absorption of the polarization plate 3 and the optical axis of the phase difference plate 2.

If the aforesaid light is incident upon a pixel in which voltage is applied to the liquid crystal layer 9 (on-state), on the other hand, the liquid crystal falls down to cause retardation corresponding to the voltage, and the state of polarization of the incident light is changed. Accordingly, the light is emitted to the outside of the liquid crystal display element without being entirely absorbed by the polarization plate 13. When the retardation comes to just $\lambda/2$, the incident right-handed circularly polarized light turns into left-handed circularly polarized light, and is emitted to the outside of the liquid crystal display element without being absorbed by the polarization plate 13. The emitted light is colored corresponding to the color

of the color filter through which it is transmitted,
and is recognized by a user.

The following is a description of the principle of
display for a reflective liquid crystal display element.

5 As shown in FIG. 3, incident light from the outside of
the liquid crystal display element passes through the
polarization plate 13 and the phase difference plate 12,
thereby turning into left-handed circularly polarized
light. The light incident upon the pixel in which no
10 voltage is applied to the liquid crystal layer 9 is
landed entire on the second and first selectively
reflective layers 6 and 4 without undergoing phase
modulation. In the second and first selectively
reflective layers 6 and 4, the left-handed circularly
15 polarized light is transmitted without being reflected
and is absorbed by the polarization plate 3, so that
black display is established.

On the other hand, the state of polarization of
the light incident upon the pixel in which voltage is
20 applied to the liquid crystal layer 9 is changed by
retardation corresponding to the magnitude of the
voltage. 70% of the right-handed circularly polarized
light components of the incident light are reflected by
the second and first selectively reflective layers 6
25 and 4, and turn again into left-handed circularly
polarized light in the liquid crystal layer 9. The
resulting light is emitted to the outside of the liquid

crystal display element through the polarization plate 13. When the retardation comes to just $\lambda/2$, the incident left-handed circularly polarized light passes through the liquid crystal layer 9, thereby turning
5 entirely into right-handed circularly polarized light. The second and first selectively reflective layers 6 reflect 70% of the right-handed circularly polarized light, so that bright display is established.

The following is a description of the viewing
10 angle of the half-transmissive liquid crystal display element according to the present embodiment. If there is a relation, $\Delta n = n_e - n_o > 0$, where n_o and n_e are refractive indexes that are perpendicular to and
parallel to the optical axis, respectively, the display
15 element is considered to have positive refractive index anisotropy, in general. If there is a relation, $\Delta n = n_e - n_o < 0$, in contrast with this, the display element is considered to have negative refractive index
anisotropy. FIGS. 4A and 4B are conceptual diagrams
20 showing the cases where the refractive index anisotropy is positive and negative, respectively.

Now let it be supposed, for each of the layers that constitute the liquid crystal display element, that the optical axis extends in a direction
25 perpendicular to the glass substrate, the average refractive index for the direction perpendicular to the glass substrate is n_e , and the average refractive index

for the direction parallel to the glass substrate is n_o . In this case, a layer with $\Delta n = n_e - n_o > 0$ is defined as a layer that has a positive refractive index, and a layer with $\Delta n = n_e - n_o < 0$ as a layer that has a negative refractive index.

According to the present embodiment, the first selectively reflective layer 4 is formed of a cholesteric liquid crystal. If refractive indexes for directions perpendicular and parallel to the major axis of the liquid crystal molecules are n_{chV} and n_{chP} ($n_{chV} < n_{chP}$), respectively, n_e and n_o are given by

$$n_e = n_{chV},$$

$$n_o = ((n_{chV}^2 + n_{chP}^2)/2)^{0.5},$$

so that the refractive index anisotropy Δn_{ch} of the first selectively reflective layer 4 is given by

$$\Delta n_{ch} = n_e - n_o$$

$$= n_{chV} - ((n_{chV}^2 + n_{chP}^2)/2)^{0.5} < 0,$$

which indicates negative refractive index anisotropy.

Further, the second selectively reflective layer 6 has a structure in which a discotic liquid crystal is twisted when it is vertically aligned. If refractive indexes for directions perpendicular and parallel to the optical axis of the liquid crystal molecules are n_{dcV} and n_{dcP} ($n_{dcV} > n_{dcP}$), respectively, n_e and n_o are given by

$$n_e = ((n_{dcV}^2 + n_{dcP}^2)/2)^{0.5},$$

$$n_o = n_{dcV},$$

so that the refractive index anisotropy Δn_{dc} of the second selectively reflective layer 6 is given by

$$\Delta n_{dc} = n_e - n_o$$

$$= ((n_{dcV}^2 + n_{dcP}^2)/2)^{0.5} - n_{dcV} > 0,$$

which indicates positive refractive index anisotropy.

When no voltage is applied, on the other hand, the liquid crystal molecules of the liquid crystal layer 9 are vertically aligned. If refractive indexes for directions perpendicular and parallel to the major axis of the liquid crystal molecules are n_{lcV} and n_{lcP} ($n_{lcV} < n_{lcP}$), respectively, n_e and n_o are given by

$$n_e = n_{lcP},$$

$$n_o = n_{lcV},$$

so that the refractive index anisotropy Δn_{lc} of the liquid crystal layer 9 is given by

$$\Delta n_{lc} = n_e - n_o = n_{lcP} - n_{lcV} > 0.$$

It can be supposed, moreover, that the phase difference plates 2 and 12 and the polarization plates 3 and 13 also have negative refractive index anisotropies (Δn_{ph} and Δn_{pol}) when synthesized. The viewing angle of the half-transmissive liquid crystal display element according to the present embodiment must be regulated in consideration of all the aforesaid refractive index anisotropies. The sum total of the products of the respective refractive index

anisotropies and thicknesses of the individual layers is defined as R_{lcd} given by

$$R_{lcd} = \Delta n_{ch} \cdot d_{ch} + \Delta n_{dc} \cdot d_{dc} + \Delta n_{lc} \cdot d_{lc} + \Delta n_{ph} \cdot d_{ph} + \Delta n_{pol} \cdot d_{pol},$$

5 where d_{ch} , d_{dc} , d_{lc} , d_{ph} , and d_{pol} are the thicknesses of the first selectively reflective layer 4, second selectively reflective layer 6, phase difference plates 2 and 12, and polarization plates 3 and 13, respectively.

10 Even if the individual layers have the aforesaid refractive index anisotropies, no phase difference is caused for light of which the optical path extends at right angles to the liquid crystal display element. Thus, in the case where the user observes the display
15 element in a direction perpendicular to it, he/she can watch display that is based on the aforesaid principle of display without regard to the value of R_{lcd} .

 In the case where the user observes the liquid crystal display element in a direction inclined at θ
20 from the direction perpendicular to the display element, the refractive index anisotropy and the layer thickness can be roughly approximated to $\Delta n \times \sin \theta$ and $d/\cos \theta$, respectively. Thus, the retardation is $\Delta n \cdot d \cdot \tan \theta$.

 FIG. 5 shows a phase difference as viewed
25 diagonally when Δn is positive. If it is supposed that there are hardly any differences in angle of incidence that are attributable to differences in

refractive index between the individual layers, the retardation of the whole liquid crystal display element is $R_{lcd} \cdot \tan \theta$. In some cases, this retardation causes a phase difference, so that the display of the liquid crystal display element may be different from the display for the case where the display element is viewed at right angles to it. In order to minimize the change of the display that is attributable to the change of the viewing angle and obtain conspicuous display, the value of R_{lcd} should preferably be minimized.

Since the refractive index changes depending on the wavelength, in general, the value of the refractive index anisotropy also changes according to the wavelength. Thus, the value of R_{lcd} also has wavelength dependence, and the viewing angle can be ideally settled in consideration of the wavelength dependence. Since the absolute values of the respective refractive index anisotropies of the elements that constitute the half-transmissive liquid crystal display element according to the present embodiment have substantially the same wavelength dependence, however, only a typical wavelength may be taken into consideration. For simplicity, the refractive index anisotropy and retardation for a wavelength of 550 nm will be described below.

According to the present embodiment, the

respective materials and thicknesses of the individual layers are designed so that we have

$$\Delta n_{ch} \cdot d_{ch} = -600 \text{ nm},$$

$$\Delta n_{dc} \cdot d_{dc} = +500 \text{ nm},$$

$$5 \quad \Delta n_{lc} \cdot d_{lc} = +500 \text{ nm},$$

$$\Delta n_{ph} \cdot d_{ph} = -137 \text{ nm},$$

$$\Delta n_{pol} \cdot d_{pol} = -275 \text{ nm}.$$

Adding up these values, we obtain

$$Plcd = -12 \text{ nm}.$$

10 In order to examine the influences of changes in color and brightness, which depend on the viewing angles of the half-transmissive liquid crystal display element and the reflective liquid crystal display element, upon the visibility of display, a subjective
15 evaluation test was conducted. A plurality of liquid crystal display elements that have different values for $Rlcd$ were prepared for this test. In this test, fifty trialists were asked to give marks for visibility with varied viewing angles to the individual display
20 elements on a five-grade basis.

FIG. 6 shows the average mark for visibility compared with $Rlcd$. The smaller the absolute value of $Rlcd$, as seen from FIG. 6, the more conspicuous the liquid crystal display elements are. It can be
25 concluded, however, that the allowable level is attained if $Rlcd$ is not greater than 50 nm.

According to the present embodiment,

$|R_{lcd}| = 12 \text{ nm}$ is given, so that the allowable level is fully reached. Thus, the display characteristic is changed less by the change of the viewing angle, so that a very conspicuous liquid crystal display element

5 can be obtained.

The present invention is not limited to the embodiment described above, and various changes and modifications may be effected therein by one skilled in the art without departing from the scope or spirit of

10 the invention. For example, the respective refractive index anisotropies and thicknesses of the individual layers are not limited to the values according to the foregoing embodiment. The values for the layers may be changed only if the absolute value of R_{lcd} for the

15 liquid crystal display element as a whole is not greater than 50 nm.

According to the embodiment described herein, the liquid crystal display element is of the half-transmissive type. However, the same effect of the

20 present invention can be displayed if the liquid crystal display element of a reflective type such that the phase difference plate 2, polarization plate 3, and backlight unit 14 are removed and that the total reflectance of the circularly polarized light

25 components in the specific direction, reflected by the first and second selectively reflective layers 4 and 6, is 100% or nearly 100%.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

5

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221